

UltraLab

Hydro's compact, self-contained, modular laboratory water system.

Benefits

- Designed for bench-top use or wall mounting
- Operates on normal tap water feed
- Deionizer capacity greater than five times that of disposable cartridges
- Easily serviceable by customer or Hydro service agreement
- Low operating costs compared to disposable cartridge systems

Features

- Portable recirculated rinse valve dispenser
- Heavy-duty polyurethane coated aluminum cabinet with easily removable access panel for servicing
- Digital temperature compensated resistivity monitor
- Triplex diaphragm pump for quiet operation
- Pressure gauge to monitor system operating pressure

Specifications:

- Dimensions: 15" W x 20" D x 23" H
- Connections: 3/8" OD tubing (feed water and drain)
- Power: 120 VAC, 130 watts
- Feed water: 35 to 100psi
- RO productions: 8 liters per hour (50 psi, 25°C)
- Pump capacity: 1.25 liters per minute

Laboratory Uses:

Critical Laboratory Applications such as Cell Culture, Cytology, Trace Analysis Work



**Produces ASTM Type 1
reagent grade water**



A33 - 8/04

CORPORATE OFFICES:

PO BOX 12197, Research Triangle Park, NC 27709

800.950.7426

www.hydroservice.com

DIVISION OFFICES:

Raleigh/Durham, NC
Rockville, MD
Pennsylvania

919.361.5188
301.770.2120
215.547.0332

New Jersey
Massachusetts
Connecticut

973.926.0203
781.337.1203
203.265.3995